



Introduction of TVI SA

Major Feature of TVI SA

- DVR Specification

		SND-04P	SND-08P	SND-16P
Video compression		H.264	H.264	H.264
HDMI / VGA resolution		1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz		
Compression resolution		Main stream: 1080P / 720P / 960H / D1 / HALF D1 / CIF		
		Sub-stream: D1 / HALF D1 / CIF		
Recording Frame		1080P / 720P / 960H / D1 / HALF D1 / CIF		
Recording resolution		1080P / 720P / VGA / WD1 / 4CIF / CIF		
Video input		BNC connector (1.0Vp-p, 75 Ω)		
Video output		1HDMI / 1VGA / 1BNC		
Audio Input / Output		1 In / 1 Out		
Alarm Input / Output		4 In / 1 Out		
Storage		2 SATA(Max. 4TB)	4 SATA(Max.4TB)	
Backup		USB / Via Network		
Power		12V DC		
Power consumption (Exclude HDD)		≤ 15W	≤ 20W	≤ 30W
Operation Temperature		-10C~+55C		
Operation humidity		10%RH ~90%RH		
Network	Interface	Ethernet port Auto detection (10/100M)	Ethernet port Auto detection (10/100/1000M)	
	Protocol	TCP/IP, DHCP, HTTP, DDNS, NTP		
	PTZ	RS-485		



Introduction of AHD SA

Major Feature of AHD SA

- DVR Specification

		SND-04AH	SND-08AH	SND-16AH
Video compression		H.264	H.264	H.264
HDMI / VGA resolution		1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz		
Compression resolution		Main stream: 1080P / 720P / 960H / D1 / HALF D1 / CIF		
		Sub-stream: D1 / HALF D1/ CIF		
Recording Frame		1080P / 720P / 960H/ D1 / HALF D1 / CIF		
Recording resolution		1080P / 720P / VGA / WD1 / 4CIF / CIF		
Video input		BNC connector (1.0Vp-p, 75 Ω)		
Video output		1HDMI / 1VGA / 1BNC		
Audio Input / Output		1 In / 1 Out		
Alarm Input / Output		4 In / 1 Out		
Storage		2 SATA(Max. 4TB)		4 SATA(Max.4TB)
Backup		USB / Via Network		
Power		12V DC		
Power consumption (Exclude HDD)		≤ 15W	≤ 20W	≤ 30W
Operation Temperature		-10C~+55C		
Operation humidity		10%RH ~90%RH		
Network	Interface	Ethernet port Auto detection (10/100M)	Ethernet port Auto detection (10/100/1000M)	
	Protocol	TCP/IP, DHCP, HTTP, DDNS, NTP		
	PTZ	RS-485		

THANK YOU!

